

Product Documentation

Product Name : **COSMONATE CG-2602N**

Kumho Mitsui Chemicals Co.,

COSMONATE CG-2602N

–Technical Data Sheet–

1. characteristics of product

Cosmonate CG-2602N is a special modified MDI, which is used for making adhesive tape for buildings and polyurethane foams in the soft ISF foam sector. Cosmonate CG-2602N is liquid at room temperature and can be stored and handled easily in the cold season. In its solvent-free form, it provides a viscosity of up to 190 cps (25°C).

2. product application



Polyurethane adhesive tape



Chair armrests (ISF)

Cosmonate CG-2602N is a special modified MDI, which is made to be proper for making polyurethane adhesive tape for buildings and soft ISF foams. It has good elongation and suitable strength in harmony and is mild in reaction, providing satisfactory moldability.

COSMONATE CG-2602N

3. Product standards & general properties

item	evaluation	UnitResult	Result
Product specifications			
NCO content	ASTM D 1638	wt%	27.3 ~ 28.3
viscosity (25°C)	ASTM D 1638	cps	90 ~ 190
specific gravity (25°C)	ASTM D 1638	-	1.23 ~ 1.25
General physical properties			
Appearance			pale brown liquid
Boiling point		°C	200 ~ 208
Freezing point		°C	below -5
Vapor pressure(25°C)		mmHg	negligible
Flash point		°C	177 ~ 218

COSMONATE CG-2602N

4. product packaging

Cosmonate CG-2602N is packed in single 230kg drum or in bulk

5. Safety and Health

Contact with the skin can cause inflammation including a rash, while contact with the eyes can cause severe pain, and visual disturbance may result in the event of excessive exposure. Inhalation of the vapor of MDI can cause bronchial asthma, headaches, or breathing difficulties, and its ingestion can cause irritation and inflammation of the gastrointestinal tract. In cases of contact with the skin, rinse the affected area completely with plenty of water or soapy water. In cases of contact with the eyes, rinse immediately with plenty of water or soapy water for 15 minutes, and seek professional medical help. In cases of MDI vapor inhalation, move the affected individual to a place where there is plenty of fresh air, keep him/her in a warm, stable condition, and perform artificial respiration if needed. In cases of ingestion, drink plenty of water, milk or raw eggs and seek medical help immediately. The risk of ignition is very low, but precautions should be taken to keep the product away from fire; in the event of a fire, extinguish with a carbon dioxide fire extinguisher. In the event of a large fire, extinguish with water.

6. Storage and Handling

The optimal storage temperature for CG-2602N is 20~35°C. Caution is needed to prevent moisture from being mixed in the storage container, which should be sealed by dry nitrogen gas if possible. When working with MDI, proper safety equipment should be worn, and a ventilation or gas mask should be used if necessary. After work, wash completely with soapy water. Contaminated work clothes should be washed and cleaned for the next use.